


# 1RU Ready HMI Engine

## 19" Full Rack Ready

### *Product Specification*

Customer	Standard		
Product Number	DMT132YYHLCMU-1D		
Customer Part Number			
Customer Approval		Date:	

#### Internal Approvals

Product Mgr	Doc. Control	Electr. Eng.
Bazile Peter	Kadafi Ali	Filip Kaczorowski
Date: 2019/03/30	Date: 2019/03/27	Date: 2019/03/23

## Revision Record

Rev.	Date	Page	Chapt.	Comment	ECR no.
A	2019-03-27	--	--	Preliminary	

PRE

## Table of Contents

<b>1.0 GENERAL DESCRIPTIONS</b>	<b>4</b>
1.1 Introduction	4
1.2 Main Features	4
1.3 Scanning Frequency	5
1.4 Input Resolution [USB]	5
1.5 Input/Output Signal	5
1.6 User Controls	5
1.7 Key Button Function	6
<b>2.0 MECHANICAL SPECIFICATION</b>	<b>7</b>
2.1 Mechanical Characteristics	7
2.2 Mechanical Drawing	8
2.3 Product Picture	9
2.4 Block Diagram	10
<b>3.0 ELECTRICAL SPECIFICATION</b>	<b>11</b>
3.1 Power consumption	11
<b>4.0 TIMING AND OPERATING SYSTEMS</b>	<b>12</b>
4.1 Timing characteristics	12
4.2 Operating systems	12
<b>5.0 OPTICAL SPECIFICATION</b>	<b>13</b>
5.1 Optical Characteristics	13
<b>6.0 ENVIRONMENTAL SPECIFICATION</b>	<b>13</b>
6.1 Environmental Characteristics	13

# 1.0 General Descriptions

## 1.1 Introduction

This industrial TFT-LCD monitor is a high performance TFT LCD monitor for rack mount products and provides a high image from the USB B Type Interface.

## 1.2 Main Features

Item	Contents
Screen Size	2 x 6.6" Diagonal
Display Format	2 x 1440(H) x RGB x 240 (V) dots
Colour	16.7M
Overall Dimensions	482.6 (W) × 44.0 (H) × 24.1 (D) mm
Active Area	344.06 mm (H) x 27.36 mm (V)
Pixel Pitch	0.114 (H) x 0.114 (V)
Viewing Angle	L/R: 160°(Typ.) U/D: 160° (Typ.)
Contrast Ratio	800: 1 (Typ.)
Brightness	750 CD/m2
I/O	3 x USB (B Type)
Backlight	LED
Mechanism	Durable Metal Case
Plug & Play	USB DisplayLink
Response time	25 msec
Touch Panel	PCT
Touch Interface	USB
Operating temperature	-10°C ~ +60°C
Storage temperature	-10°C ~ +60°C